

# F.R.L. & Silencer Installation Manual

## Silencer Kit Contents



Part/ Description	QTY
Modified FRL Unit w/ Muffler attachment	1
Twin Hoses w/ Quick Disconnect Couplers	1
jGun Hose Adapter	1
3/8" NPT Hose Connection (Inlet)	1
1/2" NPT Hose Connection (Outlet)	1

## jGun Setup

In order to install the hoses on the jGun the following items/ tools will be necessary:

- 11/16" Wrench
- 7/8" Wrench
- Hose Adapter
- 3/8" NPT Hose Connection
- 1/2" NPT Hose Connection



- Remove the ½" Coupler using the 11/16" Wrench. Afterwards remove the attachment from the bottom of the handle.



- First, Insert the ½" NPT Hose Connection into the Hose Adapter Using the 7/8" Wrench.
- Install the part until it appears to be flush with the top surface of the hose adapter (shown on the right)
- Finally, the hex MUST be oriented with the flat parallel to the step (As shown). Otherwise you will not be able to install the 3/8" Hose Connection.



- Next Insert the Hose Adapter into the jGun and position it with the ½" Hose Connection facing as shown.
- Finally Tighten 3/8" Hose Connection using an 11/16" Wrench Until it is secure



**NOTE: IF REMOVING THE SILENCER KIT FROM THE GUN REMOVE THE 3/8" NPT CONNECTOR FIRST, SO THE COUPLERS DO NOT BECOME DAMAGED.**

## F.R.L Setup



- The F.R.L. Unit will be provided as shown. Install the fittings from the Twin Hoses on the Outlet Side of the FRL Unit.



- The Male 1/2" NPT Thread is inserted into the Female NPT located on the pressurized line. The Female Hose Connector is attached to the male nipple which is extending out of the modified F.R.L. Unit. Both connectors have swivel fittings to avoid twisting the Twin Hose during install.



- When completely assembled the F.R.L. unit should appear as shown on the right.
- Make sure all Fittings are Secure especially those connected to the pressurized line.
- Finally, connect the jGun to the FRL using the Quick Disconnect Couplers and the assembly is complete.

**HYTORC**®

DIVISION OF UNEX

333 RT. 17 NORTH, MAHWAH, NEW JERSEY 07430

PHONE: 201-512-9500 FAX: 201-512-0530